

BATTERY SPECIFICATIONS

SABMA Number	Willard Cover	20 Hr Capacity Ah	Reserve Capacity Minutes	SANS CCA Amps	DIN CCA Amps	EN Rating Amps	SAE CCA Amps	IEC CCA Amps	Max Length mm	Overall Width mm	Overall Height mm	Cell Layout	Terminal Layout	Container Hold Down
331	Vented	-	-	-	-	-	-	-	-	-	-	-	-	-
333	Vented	-	-	-	-	-	-	-	-	-	-	-	-	-
309	Vented	-	-	-	-	-	-	-	-	-	-	-	-	-
320	Vented	-	-	-	-	-	-	-	-	-	-	-	-	-
610	SMF	50	77	255	220	352	370	360	255	175	213	5	A	B5
611	SMF	50	77	255	220	352	370	360	255	175	213	4	A	B5
612	SMF	45	69	220	190	309	325	310	207	175	190	4	A	B3
615	SMF	43	60	230	200	257	330	270	199	131	225	5	B	B0
615B	SMF	43	60	230	200	257	330	270	199	134	225	5	B	B1
616	SMF	43	60	230	200	257	330	270	199	131	225	4	B	B0
616B	SMF	43	60	230	200	257	330	270	199	134	225	4	B	B1
618/9	SMF	43	50	200	165	309	325	270	207	175	175	4	A	B3
621	SMF	55	85	290	250	394	415	410	255	175	213	4	A	B5
622	SMF	55	85	290	250	394	415	410	255	175	213	5	A	B5
628/9	SMF	50	62	250	205	371	390	335	244	175	175	4	A	B3
630	SMF	36	50	200	170	280	295	280	241	132	203	5	A	B0
631	SMF	36	50	200	170	280	295	280	241	132	203	4	A	B0
634	SMF	45	62	250	215	342	360	355	241	132	203	5	A	B0
636	SMF	45	62	250	215	342	360	355	241	132	203	4	A	B0
636H	SMF	45	62	250	215	342	360	355	241	132	223	4	A	B0
636T	-	-	-	-	-	-	-	-	-	-	-	-	-	-
638	SMF	70	109	345	295	523	550	485	255	175	213	5	A	B5
639	SMF	70	109	345	295	523	550	485	255	175	213	4	A	B5
640/3	SMF	60	90	325	250	428	450	395	244	175	190	5	A	B3
646	SMF	60	90	325	250	428	450	395	244	175	190	4	A	B3
649	SMF	65	97	320	260	428	450	450	233	175	222	4	A	B1
650	SMF	95	145	470	395	703	740	640	307	175	222	5	A	B0
650B	SMF	95	145	470	395	703	740	640	307	175	222	5	A	B1
650S	SMF	95	145	470	395	703	740	640	307	175	222	4	A	B0
651	SMF	60	91	325	280	437	460	460	278	175	175	4	A	B3
647/651	SMF	60	91	325	280	437	460	460	278	175	175	4	A	B3
652	SMF	70	110	400	305	561	590	500	279	175	190	4	A	B3
654	SMF	80	127	425	365	556	585	600	355	175	175	4	A	B3
657	SMF	70	110	400	340	561	590	564	278	175	190	5	A	B7
657T - 75Ah	SMF	75	120	420	350	590	620	570	278	175	190	5	A	B3
658	SMF	90	164	460	395	599	630	650	355	175	190	4	A	B3
659	SMF	80	-	-	-	-	600	-	242	175	190	4	A	B3
665	-	-	-	-	-	-	-	-	-	-	-	-	-	-
665T - 75Ah	-	-	-	-	-	-	-	-	-	-	-	-	-	-
668	SMF	80	135	430	370	561	590	610	315	175	190	4	A	B3
669	SMF	80	135	430	370	561	590	610	315	175	190	5	A	B3

BATTERY SPECIFICATIONS

SABMA Number	Willard Cover	20 Hr Capacity Ah	Reserve Capacity Minutes	SANS CCA Amps	DIN CCA Amps	EN Rating Amps	SAE CCA Amps	IEC CCA Amps	Max Length mm	Overall Width mm	Overall Height mm	Cell Layout	Terminal Layout	Container Hold Down
671	SMF	100	170	479	410	703	740	670	333	175	240	5	A	B0
674S	SMF	105	-	-	-	-	840	-	330	172	238	-	-	B1
674 - 90Ah	-	-	-	-	-	-	-	-	-	-	-	-	-	-
674	SMF	100	170	479	410	703	740	670	333	175	240	4	A	B0
674 105Ah	SMF	105	180	525	450	713	750	740	333	175	240	4	A	B0
674C 105Ah	SMF	105	-	-	-	-	840	-	330	172	238	-	A	B1
680/3/6	SMF	140	230	560	480	865	910	780	504	188	220	6	A	B0
681/2	SMF	120	216	545	465	698	735	765	504	188	220	7	A	B0
685	SMF	120	225	605	515	770	810	860	504	188	212	6	A	B0
687	SMF	210	450	1050	900	1235	1300	1400	504	273	235	-	A	B0
688	SMF	210	450	1050	900	1235	1300	1400	504	273	235	7	A	B0
689/91	SMF	140	265	690	590	879	925	975	504	220	220	6	A	B0
690	SMF	165	331	755	645	955	1005	1150	504	220	220	7	A	B0
692	SMF	165	331	755	645	955	1005	1150	504	220	220	6	A	B0
695	SMF	240	450	1130	1000	1330	1400	1480	504	273	235	6	A	B0
696	SMF	190	380	890	760	1121	1180	1310	504	220	220	6	A	B0
698	SMF	190	380	890	760	1121	1180	1310	504	220	220	7	A	B0
722	CV	50	75	255	220	352	370	360	256	175	211	5	A	B5
738	CV	70	109	345	295	456	480	485	256	175	211	5	A	B5
791 Gel	SMF	90	-	440	375	618	650	615	333	175	240	4	A	B0
791	SMF	105	180	525	450	713	750	740	333	175	240	4	A	B0
775 Gel	SMF	130	-	550	500	760	798	840	344	172	277	5	A	B0

AGM

612-AGM	SMF	-	-	-	-	-	-	-	-	-	-	-	-	-
646-AGM	CV	60	-	-	-	680	680	-	242	175	190	4	A	B13
652-AGM	CV	70	-	-	-	760	760	-	278	175	190	4	A	B13
668-AGM	CV	80	-	-	-	800	800	-	315	175	190	4	A	B13
658-AGM	CV	95	-	-	-	850	850	-	353	175	190	4	A	B13
660-AGM	CV	105	-	-	-	950	950	-	394	175	190	4	A	B13
668-AGM	CV	80	-	-	-	800	800	-	315	175	190	4	A	B13
695-AGM	CV	210	-	-	-	1200	1200	-	518	276	242	6	A	B00